

ITECH F1


60 NM DATA 2

RADIO



Catalog number	TM-IT.F1DRN660W
Application	escape route lighting
Duration time	1 h
Operating mode	NM
Version	DD - DATA2
Colour	RAL9003
Luminous flux	350 lm
Maximum light power (the luminaire can power the light source with a different power)	2 W
Active power	1.2 W
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Dimming mode	no
Temperature range	10-40 °C
Material	PC
Insulation class	2
IP	IP65
IK	IK06
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	5,1	12,8
3,0	5,5	13,8
4,0	6,0	15,4
5,0	6,7	16,7
6,0	7,0	17,8
7,0	7,1	18,9
8,0	7,5	19,6
9,0	7,9	19,8
10,0	8,1	20,0

