


ITECH W1 60 NM AT



Catalog number	TM-IT.W1ATN660W
Application	lighting of the final exit / fire-protection devices
Duration time	1 h
Operating mode	NM
Version	AT - auto-test / self-test
Colour	RAL9003
Luminous flux	299 lm
Maximum light power (the luminaire can power the light source with a different power)	2 W
Active power	1.2 W
Power supply	210+250 V AC 50+60 Hz
Power supply CB	186+254 V DC
Dimming mode	no
Temperature range	10-40 °C
Material	PC
Insulation class	2
IP	IP65
IK	IK06
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	3,3	7,9
3,0	3,5	8,4
4,0	3,4	8,6
5,0	3,4	8,7
6,0		
7,0		
8,0		
9,0		
10,0		

