


TM.ONTEC C C1H 03 CBA



Catalog number	TM-OC.CHCBA000W
Application	escape route lighting
Duration time	-
Operating mode	-
Version	for central battery
Colour	RAL9003
Luminous flux	353 lm
Maximum light power (the luminaire can power the light source with a different power)	3 W
Active power	6.5 W
Power supply	210+250 V AC
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	-10-40 °C
Material	PC
Insulation class	2
IP	IP20
IK	IK03
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Standards	PN-EN 60598-1, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	9,7	21,0
3,0	10,9	24,0
4,0	12,9	29,6
5,0	14,1	34,3
6,0	11,5	36,0
7,0	6,5	36,5
8,0	4,9	28,0
9,0	4,7	23,5
10,0	4,5	15,5

