



ONTEC S M2

102 M DATA 2 COLD



Active power	6.6 W
Operating mode	M
Maximum light power (the luminaire can power the light source with a different power)	4.7 W
Colour	RAL9005
Duration time	1 h
Battery	LiFePO4/C 6.4V 1.5Ah
Standards	PN-EN 60598-1, PN-EN 60598-2-2, PN-EN 60598-2-22, PN-EN 61347-1, PN-EN 61347-2-7, PN-EN 61347-2-13, PN-EN 55015, PN-EN 61000-3-2, PN-EN 62031, PN-EN 62471, PN-EN 1838
Power supply	210÷250 V AC 50÷60 Hz
Power supply CB	186÷254 V DC
IK	IK08
Version	DD - DATA2
IP	IP65
Application	anti-panic lighting
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB
Insulation class	2
Temperature range	-15÷40 °C
Luminous flux	241 lm
Material	PC
Dimming mode	yes
Catalog number	TM-OS.M2DDM16CB





PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	3,6	9,5
3,0	3,8	10,4
4,0	4,2	11,8
5,0	4,6	13,0
6,0	4,7	13,9
7,0	4,6	14,8
8,0	4,6	15,3
9,0	4,3	15,8
10,0	4,0	16,0

