

TM.ONTEC S20 M2X CBA



Catalog number	TM-S2.MXCBA060W
Application	anti-panic lighting
Duration time	-
Operating mode	-
Version	for central battery
Colour	RAL9003
Luminous flux	154 (L); 309 (H) lm
Active power	5.4 W
Power supply	210+250 V AC
Power supply CB	186+254 V DC
Dimming mode	yes
Temperature range	-10-40 °C
Material	PC
Insulation class	2
IP	IP65/IK08
IK	IK08
Battery	Un[V] DC 186-254
Warranty	24 months - ST 36 months - AT 60 months - DATA, CB



PHOTOMETRY [m]

Ceiling height	Distance wall - fitting	Distance fitting - fitting
2,5	3,0 - CB L 3,5 - CB H	7,0 - CB L 8,0 - CB H
3,0	3,5 - CB L 3,5 - CB H	8,0 - CB L 9,0 - CB H
4,0	4,0 - CB L 4,5 - CB H	9,5 - CB L 11,0 - CB H
5,0	4,0 - CB L 5,0 - CB H	11,0 - CB L 12,5 - CB H
6,0	3,5 - CB L 5,0 - CB H	12,5 - CB L 14,5 - CB H
7,0	3,5 - CB L 5,0 - CB H	13,5 - CB L 16,0 - CB H
8,0	3,5 - CB L 5,5 - CB H	14,0 - CB L 17,0 - CB H
9,0	3,0 - CB L 5,5 - CB H	14,5 - CB L 18,0 - CB H
10,0	2,0 - CB L 5,0 - CB H	15,0 - CB L 19,0 - CB H

